



KEY

Cone

Sign

Work area

Closed area

Traffic light head

Traffic light phase

Diversion route

DETAIL B

Single/Dual carriageway 40mph or less - 450mm traffic cones, spacing 1.5m.  
Single/Dual carriageway 50mph or more - 750mm traffic cones, spacing 1.5m.  
Dual carriageway national speed limit - 750mm traffic cones, spacing 1.5m, relaxation 3m.

Notes:  
1) During darkness, warning lights to BS EN 12352:2006 should be provided in accordance with Table A1.3 (Appendix 1).  
2) 45 degree tapers have 1.5m spacing and no relaxations.  
3) On motorways and NSL AP duals with hard shoulders, 1m cones will be required for both standard and relaxation works for lead tapers and the facing wall of lane changes.

DETAIL C2

Single carriageway 40mph or less - 450mm traffic cones.  
Single/Dual carriageway 50mph or more - 750mm traffic cones.

Notes:  
1) During darkness, warning lights to BS EN 12352:2006 should be provided in accordance with Table A1.3.

Lane 1 Closure or Shuttle Lane With Ped Walkway

Min width of sideways safety zone (S) 0.5 m  
Min length of longways clearance (L) 0.5 m  
Speed of the road 30

| Rev       | Description | By | Chk | Date |
|-----------|-------------|----|-----|------|
| Revisions |             |    |     |      |

Client:  

nationalgrid

Project:  
A34 Birmingham Road,  
Great Barr, B43 6NR  
Grid Ref: (x)404598 ; (y)294245

Title:  
Temporary Lane 1 Closure and  
Road closure / diversion

DOOCEY

Traffic Management

|                  |                  |                  |
|------------------|------------------|------------------|
| Design: AW       | Drawn: AW        | Chkd: PO         |
| Date: 15/05/2025 | Date: 15/05/2025 | Date: 15/05/2025 |
| Scale: A3 - NTS  | Status: Proposed |                  |

Drawing No  
DTM25842 - 001

Rev:  
-

PEDESTRIAN WALKWAY DETAIL