

KEY

- Cone
- Sign
- Work area
- Traffic light head
- Pedestrian light head
- Traffic light phase

DETAIL B

Single/Dual carriageway 40mph or less - 450mm traffic cones, spacing 1.5m.
Single/Dual carriageway 50mph or more - 750mm traffic cones, spacing 1.5m.
Dual carriageway national speed limit - 750mm traffic cones, spacing 1.5m, relaxation 3m.

Notes:
1) During darkness, warning lights to BS EN 12352:2006 should be provided in accordance with Table A1.3 (Appendix 1).
2) 45 degree tapers have 1.5m spacing and no relaxations.
3) On motorways and NSL AP duals with hard shoulders, 1m cones will be required for both standard and relaxation works for lead tapers and the facing wall of lane changes.

DETAIL C2

Single carriageway 40mph or less - 450mm traffic cones.
Single/Dual carriageway 50mph or more - 750mm traffic cones.

Notes:
1) During darkness, warning lights to BS EN 12352:2006 should be provided in accordance with Table A1.3.

Min width of sideways safety zone (S)	0.5 m
Min length of longways clearance (L)	0.5 m
Speed of the road	30

Rev	Description	By	Chk	Date
Revisions				




Client:
nationalgrid

Project:
Greet's Green Road,
West Bromwich, B70 9EP
Grid Ref: (x)398532 ; (y)291500

Title:
Temporary Three Way
Traffic Lights & One Way Road
Closure & Diversion



Design: JJO	Drawn: JJO	Chkd: OP
Date: 11/09/25	Date: 11/09/25	Date: 11/09/25
Scale: A3 - NTS	Status: Proposed	
Drawing No	DTM7704 - 001	
		Rev: -

Traffic Light Phase Timings			
Phase 1: Greet's Green Road, (W)	Red	20s	
	Green	45s	
Phase 2: Greet's Green Road, (E)	Red	20s	
	Green	45s	
Phase 3: Ryders Green Road, (S)	Red	20s	
	Green	45s	
Note: Timings may only be adjusted by a competent operative to suit traffic conditions if required			