Note:

Drawing to run in conjunction with drawing 1817547.0001

ROAD AHEAD CLOSED

Diversion

ROAD CLOSED

ROAD AHEAD CLOSED

ROAD AHEAD CLOSED

ROAD AHEAD CLOSED

Diversion ENDS

ROAD AHEAD CLOSED

Diversion

ROAD AHEAD CLOSED

Diversion

ROAD AHEAD CLOSED ACCESS ONLY

ROAD AHEAD CLOSED

Diversion ENDS

Diverted traffic

Diverted traffic

Diverted traffic

Diverted traffic

SHRUBBERY AVENUE

CASTLE ROAD

HENHILL ROAD

DUDLEY ROAD

WADES CLOSE

Royston

Campion Court

Tolsarne

Shrubbery

Woodlands

Heidi

Shelter

Depot

Horses (PH)

Tks

149.7m

150.0m

Go Traffic Management

This drawing has been produced for a specific client & project identified below and is not intended for use by any other person or for any other purpose. © Go Traffic Management

Risks

1. Design completed from information provided + google maps desktop risk assessment
2. Cone lamps must be used on all road with A speed limit of 40mph or more.

Notes

1. All signs as per Chapter 8. Distances between cones to be 9m maximum unless otherwise noted.
2. Distances between signs NOT to scale for purpose of clarity.
3. All sign placement subject to available safe working space.
4. The purpose of the Traffic Management Plan is for it to be used only as a guide and all traffic management equipment should be put out according to the 'Safety at Street Works and Road Works – Code of Practice', i.e. Red Book & the 'Traffic Signs Manual Chapter 8', i.e. Yellow Book.
5. Signs must be placed in accordance with TSM and the scheme RAMS pack.
6. Site conditions may have changed since the design of the drawing any changes which subsequently affect the design need to be reported by the Traffic Management Operative & any changes implemented must comply with Chapter 8.

DETAIL B

1. Single/Dual carriageway 40mph or less - 450mm traffic cones, spacing 1.5m.
Dual carriageway 50mph or 60mph - 750mm traffic cones, spacing 3.0m.
Dual carriageway national speed limit - 750mm traffic cones, spacing 1.5m, relaxation 3m.

TYPE 3
Portable cylindrical, warning lights to BS EN 12352:2006 should be provided in accordance with Table A1.3 (Appendix 7).
2) 40" beams have 1.2m spacing, no relaxation.
3) Where traffic cones are used to channel vehicles, no cones will be required for both standard and relaxation works for field layers and the factory wall of lane changes.

Key

Sign position and aspect of vision	
Cones	
Working space	VULNERABLE ROAD USERS ACCESS MAINTAINED
OS Work area	
Diversion Route 1	
Diversion Route 2	

Shrubbery Ave closed diversion via

Menin Rd <> Castle Rd <> Dudley Rd

DIVERSION ENDS

Traffic Management must comply with The Safety at Street Works and Road Works Code of Practice

ROAD SPEED

30

SPECIAL SIGNAGE

DO NOT SCALE FROM THIS DRAWING.

ROAD CLOSURE

REV.	DATE	DESCRIPTION
A	12.06.26	AS DRAWN

GTM Go Traffic Management

Head Office: Go Traffic Management, Chaddock Lane, Worsley, Manchester, M28 1XW
Tel: 0161 351 5370
www.gtm.co.uk

CERTIFIED ISO 9001 · ISO 14001 OHSAS 18001

TRAFFIC MANAGEMENT PLAN

Client: SEVERN TRENT Customer Solutions Plus — Waste Infra Network Services

Drawing Number: 1817547.0002

Drawing Title: SHRUBBERY AVENUE, DY4 8DL

	Design:	Technical Officer:	REV:
Name:	CR	CR	A
Signature:			
Date:	12.06.26	12.06.26	

BASED UPON THE ORDNANCE SURVEY MAP WITH THE PERMISSION OF THE CONTROLLER OF H.M STATIONERY OFFICE.